


## Features


- Double cells in series
- Higher voltage
- RoHS compliant
- Consumer electronic
- AMR
- DC-DC converters



Items	Characteristics		
Rated Voltage	5.5V		
Operating Temperature Range	-40 ~+65°C (-40 ~+85°C@4.6V)		
Surge Voltage	5.7V		
Capacitance Range	0.5~5F		
Capacitance Tolerance (25°C)	-10~+30%		
Temperature Characteristics	The specifications shall be met at category temperature range form -40°C to 65°C	Capacitance Change	Within 30% of the value at 25°C
		ESR	Less than 2 times of the initial specified value
High Temperature Loaded	The specifications shall be met after rated voltage applied at 65°C for 1000 hours	Capacitance Change	Within 30% of the initial value
		ESR	Less than 2 times of the initial specified value
High Temperature Storage	The specifications shall be met after storage at 65°C for 1000 hours	Capacitance Change	Within 30% of the initial value
		ESR	Less than 2 times of the initial specified value
Cycle Life	The specifications shall be met after 500,000 cycles at 25°C, cycle of charge/discharge from $V_R$ to $1/2V_R$	Capacitance Change	Within 30% of the initial value
		ESR	Less than 2 times of the initial specified value

## Dimensions

mm



## Standard Ratings for SRM Series

$U_R$ (Surge Voltage) Code	Rated Capacitance 25°C	Impedance		Leakage Current (72hrs)	Size W×L×H	F	d	P/N
		ESR <sub>DC</sub>	ESR <sub>AC</sub> 1KHz					
(V)	(F)	(mΩ)	(mΩ)	(mA)	(mm)	(mm)	(mm)	-
5.5 (5.7) 5R5	0.5	800	400	0.008	8.5×17×17	12/5.0	0.6	SCMDMR5R5504QRH081717E
	1	500	260	0.010	8.5×17×17	12/5.0	0.6	SCMDMR5R5105QRH081717E
	1.5	300	160	0.012	8.5×17×23	12/5.0	0.6	SCMDMR5R5155QRH081723E
	2.5	260	140	0.016	11×21×23	15.5/5.5	0.6	SCMDMR5R5255QRH112123E
	3.5	160	110	0.02	11×21×27	15.5/5.5	0.6	SCMDMR5R5355QRH112127E
5	120	80	0.03	13×26×27	18/8.0	0.6	SCMDMR5R5505QRH132627E	